

AMENDMENT TO THE CLAIMS:

9. (Currently Amended) A loader disposed in a low cleanliness room in a border between the low cleanliness room and a high cleanliness room having a higher pressure than the ~~lower-low~~ cleanliness room, the loader comprises:

- a movable stage for mounting a container;
- an opening portion in a wall that separates the low cleanliness room from the high cleanliness room and through which a dust free article is transported between an inside of the container and the high cleanliness room;
- a door for opening and closing the opening portion;
- a unifying means for unifying a cover of the container and the door;
- a driving apparatus for moving the cover and the door together within the loader to simultaneously open and close the opening portion and the container; and
- a gap provided between the opening portion and the door through which air flows out from the high cleanliness room to the lower cleanliness room to prevent dust flowing into the high cleanliness room.

10. (Canceled)

11. (Currently Amended) The loader of claim 9, wherein the driving apparatus is provided within a space formed by a front cover and a wall for the driving apparatus.

12. (Previously Presented) The loader of claim 9, wherein the cover and the door are adapted to move vertically together within the loader.

13. (Previously Presented) The loader of claim 9, wherein the container mounted on the stage approaches the door horizontally.

14. (Currently Amended) The loader of claim 9, wherein the unifying means for unifying the cover and the door comprises:

a pin to be inserted in a hole formed in a protrusion arranged on the outside of the cover;

another pin to be inserted in another hole formed in the door; and

a driving mechanism for simultaneously moving both of the pin and the another pin to unify the cover and the door.

15. (Previously Presented) The loader of claim 9, which further comprises a driving device for moving the container mounted on the stage to the door.

16. (Currently Amended) A container for receiving and transporting a dust free article therein and to be mounted on a loader, the loader is provided with an opening portion disposed in a low cleanliness room in a border location between a high cleanliness room and the low cleanliness room having a lower pressure than the high cleanliness room and a door for opening and closing the opening portion, the container comprises:

an opening port through which the dust free article is transported between an inside of the container and the high cleanliness room;

a cover which covers the opening port and is unified with the door of the loader, the cover and the door are adapted to move together within the loader to open and close the opening portion; and

a fixing means for fixing the cover to the opening port when the dust free article is enclosed in the container for transportation.

17. (Previously Presented) The container of claim 16, wherein the cover of the container, unified with the door of the loader within the loader, moves vertically.

18. (Previously Presented) The container of claim 16, wherein an angle formed by an outward normal line of a surface on which the opening port is closely contacted with the cover and a descending direction of the cover unified with the door of the loader, forms an acute angle.

19. (Previously Presented) The container of claim 16, which further comprises a sealing material for closing both of the cover and the opening port.

20. (Previously Presented) The container of claim 16, which further comprises a positioning means to position the container in relation to the loader when the container is mounted on the loader.

21. (Previously Presented) The container of claim 16, which further comprises a handle to support the container when the container is transported.

22. (Previously Presented) The container of claim 16, which further comprises a protrusion formed on an outer portion of the cover, the protrusion having a hole to which a pin is inserted for unifying the cover and the door of the loader.

23. (Previously Presented) The container of claim 16, which further comprises an air cleaning device.

24. (Currently Amended) An apparatus for transporting a dust free article, which comprises:

a loader for transporting the dust free article between an inside of a container and the high cleanliness room, said loader disposed in a low cleanliness room in a border portion between a high cleanliness room and a low cleanliness room having a lower pressure than the high cleanliness room, ~~which transports the dust free article between an inside of a container and the high cleanliness room,~~ the loader comprises:

a movable stage for mounting the container to transport the dust free article;

an opening portion through which the dust free article is transported between the high cleanliness room and the container;

a door for opening and closing the opening portion, which is provided with a gap between the door and the opening portion;

a unifying means for unifying a cover of the container and the door when the container approaches the door; and

a driving apparatus for opening and closing the opening portion of the loader and the container by moving the unified cover and door within the loader; and

wherein the container comprises:

an opening port through which the dust free article is transported between an inside of the container and the high cleanliness room;

a cover which covers the opening port of the container and is to be unified with the door of the loader, the cover and the door are adapted to move within the loader to open and close the opening port of the container; and

a fixing means for fixing the cover to the opening port of the container when the dust free article is set in the container and is transported.

25. (Previously Presented) The apparatus of claim 24, wherein the cover, unified with the door of the loader within the loader, moves vertically.

26. (Previously Presented) The apparatus of claim 24, wherein the driving apparatus for opening and closing the opening portion of the loader and the container by moving the unified cover and door within the loader is disposed within a space formed by a front cover and a wall for the driving apparatus.

27. (Previously Presented) The apparatus of claim 24, wherein the loader further comprises a driving device for causing the container mounted on the stage to approach the door.

28. (Previously Presented) The apparatus of claim 24, wherein the container further comprises an air-cleaning device.

29. (Previously Presented) A method for transporting a dust free article, using a loader, provided with a movable stage, a door, a unifying means and a driving means, disposed in a low cleanliness room in a border portion between a high cleanliness room having a higher air pressure than that of the low cleanliness room, and a container receiving the dust free article to be transported, which comprises:

mounting the container receiving the dust free article on the movable stage disposed on the loader;

causing the container to approach the door of the loader for opening and closing an opening portion of the loader;

unifying a cover of the container and the door of the loader;

moving the cover and the door unified within the loader to open the opening portion of the loader and the container; and

transferring the dust free article received in the container from an inside of the container to the high cleanliness room through the opening portion of the loader.

30. (Previously Presented) The method of claim 29, further comprising:
fixing the container mounted on the movable stage to the movable stage to
unify the container in the movable stage; and
wherein causing the container to approach the door of the loader for opening
and closing the opening portion of the loader is done by moving the movable stage
by a driving device in the loader.

31. (Previously Presented) The method of claim 29, wherein the cover of the
container and the door of the loader unified within the loader is moved vertically.

32. (Currently Amended) A loader comprising:
a movable stage for mounting a container, the container is disposed in a low
cleanliness room, ~~the a~~ high cleanliness room having a higher pressure than the low
cleanliness room;
~~an opening portion through which a dust free article is transported between an~~
~~inside of the container and a high cleanliness room;~~
a door for opening and closing the an opening portion for transporting a dust
free article between an inside of the container and a high cleanliness room;
a unifying means for unifying a cover of the container and the door; and
a driving apparatus for moving the cover and the door together within the
loader to simultaneously open and close the opening portion and the container.

33. (New) The loader of claim 9, wherein the driving apparatus is provided
within a space formed by a front cover and a wall for driving apparatus and the cover
and the door are adapted to move vertically with the space.

34. (New) The loader of claim 9, further comprising a second driving apparatus
that is adapted to move the movable stage in a horizontal direction toward and away
from the opening portion in the wall.